

TEST REPORT

Report No. : GR:TX:1410007606

TAJ VELVET & SILK MILLS. 61 INDUSTRIAL ESTATE, NUNHAI AGRA-282006

INDIA

CONTACT PERSON : RAVI VERMA

DATE: 18/01/2010

CUR-340

THE FOLLOWING SAMPLE(S) WAS/WERE SUBMITTED AND IDENTIFIED BY/ON BEHALF OF THE CUSTOMER AS:

SAMPLE DESCRIPTION FABRIC

RI

WOVEN COTTON VELVET

LAB. IDENTIFIED COLOUR COUNTRY OF ORIGIN SAMPLE RECD ON

TEST(S) REQUIRED

BLACK INDIA

TEST START DATE

16/01/2010

TEST END DATE

18/01/2010

14/01/2010 FLAMMABILITY

CONCLUSION

THE SAMPLE TESTED MEETS THE REQUIREMENTS BS 5867 PART 2 2008 TYPE B PERFORMANCE

per pro SGS India Private Ltd.

Authorised Signatory

Gadadhar Panda Executive

JOE No.: 1041804191

Page -1 of 2

Contro! No. 1415011219

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at ntp://www.sgs.com/terms_and_conditions.htm and and Terms and Conditions for electronic documents www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of iability, independing and jurisdiction is sues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this socument is unlawful and offenders may be prosecuted to the fullest extent of the law.



TEST REPORT

Report No.: GR:TX:1410007606

DATE: 18/01/2010

CUR-340

Specification for Curtains & Drapes [BS 5867: Part 2:2008]

Flammability requirement: Type B performance

Conditioning: The samples were conditioned in an atmosphere having a temperature of 20±2°C and a

Relative humidity of 65±5%.

Results: These results may not apply to situations where there is restricted air supply or prolonged

exposure to large sources of intense heat as in a conflagration.

Flame application time : 15 s	Length			Width		
	1	2	3	1	2	3
Flame reached an edge :	No	No	No	No	No	No
Hole reached an edge :	No	No	No	No	No	No
Flaming debris :	No	No	No	No	No	No

Requirements: No part of any hole nor any part of the lowest boundary of any flame shall reach the upper edge of either vertical edge of any specimen, and there shall no separation of flaming debris

**** End of Report****

JOE No.: 1041804191

Page -2 of 2

Control No 1415011219

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at http://www.sgs.com/ferms_eq-document.htm. Attention is drawn to the limitation of isability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction form exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.